



Current Status and Future Prospects of ULTIMATE-START :

Laser Tomography Adaptive Optics for the Subaru Telescope

Aino Narayama (M2),
Masayuki Akiyama,
Hiyori Tanabe, Mitsuaki Takahashi,
Ayumi Ishikawa, Takeru Hayashi
(Tohoku University),
Yosuke Minowa, Yoshito Ono, Koki
Terao, Shin Oya(NAOJ),
Hajime Ogane(NAOJ, ANU),
Jesse Cranney(ANU),
Tomoyasu Yamamuro(Optcraft)

What is ULTIMATE-START ?

2



ULTIMATE-START is prototype of ULTIMATE Subaru, providing a narrow-field LTAO mode in ULTIMATE



Project to implement **Laser Tomography Adaptive Optics (LTAO)** on the **Subaru Telescope**.

Feature

① Use 4 LGS & 4 WFS

- Laser light source (589nm, TOPTICA) divided into **4 LGS**
- LGS asterism diameters are selectable from **10", 20", 30", 40"**


② DM upgrade

- 188DM → **ALPAO 64 × 64DM** : enable much finer wavefront corrections



©国立天文台

Goal of ULTIMATE-START



Goals :

- Achieve diffraction-limited performance in the **visible and near-infrared (NIR)** bands
- Attain a FWHM of **0.02 arcsec at 600 nm**

Science goals :

- Advance understanding of **galaxy formation and evolution**
 - Star formation
 - Galaxy mergers
 - The role of AGN feedback


What is LTAO ?

Conventional Subaru AO system

SCAO

Single Conjugate Adaptive Optics

- **Only one laser guide star (LGS)** is used.
- There are areas where the wavefront cannot be measured, reducing the correction accuracy
→ **Cone effect**



ULTIMATE-START


LTAO

Laser Tomography Adaptive Optics

- Reduces the cone effect and improves AO correction performance
- Use multiple LGSs and estimate wavefront at each altitude


Overview of LTAO

- Light from the telescope passes through **AO188**, then through **LTAO**,
- And is subsequently directed to each instrument via the **NBS**




Instruments:

- **IRCS** (Infrared Camera and Spectrograph)
- **SCEXAO** (Coronagraphic ExAO)
- **NINJA** (High-sensitivity, wide-band spectrograph) : currently being installed
- **3D II** (Visible IFU) : planned for future installation



Installation : August 6–22, 2025



Alignment work on Obs floor



Pre-focal optics

LGS-WFS × 4

Offner relay optic × 4



Period : August 6-22, 2025

✓ **Alignment of individual optical systems under summit environmental conditions**


- Pre-focal optics
- Four LGS wavefront sensors (LGS-WFSs)
- Four Offner relay optics

Installation : August 6–22, 2025


Installation work on NsIR



Optical axis alignment process using the AO3k alignment laser and the frame hexapod



Final :
WFS Image Check
Confirmed proper light injection into each WFS.
Verified 32×32 sub-apertures on all sensors.



Period : August 6-22, 2025


- ✓ Alignment of individual optical systems
- ✓ **Installation and alignment on the common platform**
- ✓ **System testing and data acquisition**

First onsky observation

Details on P06:Akiyama-san

Date : December 3, 8

- Truth WFS loop close with NGS
- Acquisition test of 4 laser guide stars



- Truth WFS Loop Close with NGS → **Success !**




Fig 1 : Taken by IRCS

DM Loop close test	NGS	LGS
Truth WFS	○	
LGS WFS (one by one)	○	TBC
4LGS WFS		TBC

- LGS WFS Loop Close Test with NGS → **Success !**
- LGS Loop Close Test with 1LGS WFS → TBC
- Acquire 4LGS to 4LGS-WFS and close **LTAO loop** → TBC (4 LGS were acquired with offsets)

Tip-Tilt correction with machine learning approach

- Trying to apply **reinforcement learning to Tip-Tilt mirror for achieving 0.003" TT residual**

Control value


PID
$$u(t) = \underbrace{K_p e(t) + K_i \int_0^t e(t) d\tau + K_d \frac{de(t)}{dt}}_{\text{PID gain parameter}} \quad (e(t): \text{error})$$

Provides reactive control based on current and historical error signals.
Controller performance depends on gain tuning.

Reinforcement learning

$$V_{\pi}(s) = \mathbb{E}_{\pi} [R_{t+1} + \gamma R_{t+2} + \gamma^2 R_{t+3} + \dots | S_t = s]$$

Learns an **optimal policy** that maximizes the expected cumulative future reward $V_{\pi}(s)$.
Achieves advanced control strategies by leveraging historical turbulence measurements and delay information.



State
= error from past 5 steps
+ previous action

Reward
= - error²

Action
= TTM target voltage

Agent [Recurrent PPO with LSTM]


learns the optimal policy to maximize rewards.

Run #	Smoothed	Value	Step	Relative
RecurrentPPO_2	-999.6133	-985.0197	100,352	4.291 min
RecurrentPPO_3	-331.8713	-322.4096	100,352	3.545 min


Learning curve
x : training time
y : average reward

Tip-Tilt correction with machine learning approach

Results with RL
3.25 → 0.32 (9.85%)



Results with optimal PID
($K_P=0.85$, $K_I=0.008$, $K_D=0.08$)
3.34 → 0.28 (8.50%)



Under the current setup, reinforcement learning and PID control exhibit **comparable performance**. **Future work** includes improving the reinforcement learning model and tuning hyperparameters.

Summary

✓ Achievements in 2025

- **Installation & First Light:** Completed LTAO installation and achieved first light.
- **Demonstrated Performance:** Successfully acquired calibration data and demonstrated AO loop close using an NGS & the Truth WFS.

🎯 Next Steps (June 2026)

- **Full LTAO Loop Close:** Acquire 4 LGSs to 4 LGS-WFSs simultaneously and aim to achieve full LTAO loop close in the next engineering observation.



As an early career researcher

- Experiencing instrument integration and commissioning at the summit gave me insights that cannot be obtained through simulations alone.
- I learned the importance of flexibility and problem-solving in real operational environments.
- I also came to appreciate the collaborative effort required to support world-class astronomical observations.
- This experience has further motivated me as an instrument developer, and I am deeply grateful for the opportunity.